

## RESISTENCIA de CARGA [kg] s/dimensional

modelo	diam	alto	diam tornillo	lt.	carga
	[mm]	[mm]	[mm]	[mm]	[kg]
10--10	10	10	4	10	10
10--15	10	15	4	10	8
15--8	15	8	4	10	20
15--15	15	15	4	10	20
20--10	20	10	6	13	30
20--15	20	15	6	13	25
20--20	20	20	6	18	25
20--25	20	25	6	18	25
25--15	25	156	6	20	40
25--20	25	20	6	20	50
25--22	25	22	8	20	40
25--25	25	25	6	20	40
25--30	25	30	6	20	35
25--30	25	30	8	20	35
30--10	30	10	8	50	90
30--15	30	15	8	20	90
30--20	30	20	8	20	90
30--30	30	30	8	20	80
30--40	30	40	8	20	60
40--20	40	20	8	20	160
40--30	40	30	8	20	150
40--30	40	30	10	25	150
40--40	40	40	8	20	120
40--40	40	40	10	25	120
50--30	50	30	10	30	250
50--35	50	35	10	25	230
50--40	50	40	10	30	220
50--50	50	50	10	25	200
60--25	60	25	10	30	400
60--35	60	35	10	30	350
60--45	60	45	10	30	300
75--25	75	25	12	35	650
75--40	75	40	12	35	500
75--45	75	45	12	35	500
75--55	75	55	12	35	450
100--40	100	40	16		1200
100--60	100	60	16	45	1100
100--75	100	75	16	45	1000
150--75	150	75	16	45	2000
200--100	200	100	20	45	3000